

METHOD FOR FABRICATING WAVEGUIDES

[0001] The present invention relates generally to fabricating planar waveguide structures, and particularly to fabricating silicon germanium(SiGe) waveguide structures.

5

BACKGROUND OF THE INVENTION

[0002] The advent of the information age has seen an increasing drive toward extremely high-speed applications, leading to an increasing use of optical circuits in communication systems. Planar optical waveguides are widely used as components in optical communication systems. A typical planar waveguide structure comprises a lower cladding region, a light guiding core region and an upper cladding region. The light guiding core region has a higher index of refraction than either the lower or the upper cladding regions.

10

[0003] SiGe waveguides are of particular interest because both optical and electronic devices can be integrated on a single silicon substrate. Silicon is a well established substrate for electronic circuits, and high quality silicon is readily available at low cost. Additionally, both Si and SiGe are transparent in the 1300 nm and 1500 nm telecommunications wavelengths and further, SiGe has a higher index of refraction than Si. Finally, the optical and electrical properties of SiGe waveguides can be adjusted by varying the Ge concentration.

15

[0004] Although, SiGe waveguide structures are desirable for their electrical and optical properties, several problems exist with fabricating low loss SiGe waveguides. Generally, a SiGe waveguide structure comprises a lower cladding primarily composed of silicon, a silicon germanium core and an upper cladding also composed primarily of silicon. The lattice constant of Ge is 4% larger than that of Si. Thus, when SiGe is grown on pure silicon, this difference in lattice constants may cause very high misfit and threading dislocation densities in the structure. These dislocations may lead to increased optical losses in the waveguide structure.

20

[0005] Moreover, in a typical SiGe waveguide structure, the distribution of Ge in the vertical direction is different from the distribution of Ge in the horizontal direction. This asymmetry leads to birefringence effects. Generally, a light wave traveling down a waveguide comprises two orthogonally polarized modes, one perpendicular to the substrate and the other parallel to the substrate. In conventional SiGe waveguide structures, the

25

30

perpendicular mode sees a different index of refraction from the parallel mode, leading to a dispersion of the transmitted signal.

[0006] Additionally, waveguide structures used for optical telecommunications typically require core thicknesses in the range of 2-10 μm . Current methods of producing SiGe waveguide structures are very slow and impractical for growing SiGe waveguide structures of such thicknesses. Further, such slow growth processes may increase the amount of contaminants in the waveguide structure. These contaminants may also contribute to optical losses in the waveguide structure.

[0007] Therefore, there is a need in the art for a low loss SiGe waveguide fabrication process that is suitable for large scale production of SiGe waveguide structures.

SUMMARY OF THE INVENTION

[0008] There are several embodiments of the invention.

[0009] In one embodiment of the invention, a method of forming a planar waveguide structure comprises forming a first graded layer on a substrate, wherein the first graded layer comprises a first and a second optical material, wherein the concentration of the first optical material increases with the height of the first graded layer; and forming a second graded layer on the first graded layer, the second graded layer comprising the first and second optical materials wherein the concentration of the first optical material decreases with the height of the second graded layer. The method may also include forming a blocking layer between the substrate and the first graded layer and forming an upper cladding layer over the second graded layer.

[0010] In one embodiment, the method may also include forming a uniform layer between the first and second graded layers, the uniform layer containing first and second optical materials wherein the concentration of the first optical material is constant. In another embodiment, the uniform layer is formed directly over the substrate and a cladding layer may be formed directly over the uniform layer. This embodiment may also include a blocking layer between the substrate and the uniform layer. In yet another embodiment, a uniform layer is formed directly over the substrate, a graded layer is formed immediately over the uniform layer and a cladding layer is optionally formed over the graded layer.

[0011] In one embodiment, the first optical material is germanium and the second optical material is silicon. In one embodiment, the blocking layer, the first and second graded layers, the uniform layer and/or the cladding layer are formed epitaxially.

[0012] Optionally, the method also includes etching a pattern in the substrate and then forming the blocking layer, graded layers and uniform layer, if used, so as to conform to the shape of the pattern.

[0013] In another embodiment, the etching step is performed after the first graded layer and the uniform layer are formed. In this embodiment, the pattern is etched into the uniform layer and the first graded layer and the second graded layer is then formed over the patterned etched layers. In embodiments that do not contain the uniform layer, the pattern is etched into the first graded layer and then the second graded layer is formed over the etched patterned first graded layer. In embodiments that do not contain the first or second graded layers, the pattern is etched in the uniform layer, and an upper cladding layer is optionally formed on the etched patterned uniform layer.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] Additional objects and features of the invention will be more readily apparent from the following detailed description and appended claims when taken in conjunction with the drawings, in which:

[0015] Figure 1 is a diagram of an exemplary reactor that may be used to implement the present invention.

[0016] Figure 2 illustrates a waveguide structure that may be fabricated in accordance with an embodiment of the invention.

[0017] Figure 3 illustrates concentration profiles of waveguide structures fabricated in accordance with the invention.

[0018] Figure 4 is a flow chart of the processing steps used to fabricate waveguide structures in accordance with an embodiment of the invention.

[0019] Figure 5 illustrates schematic cross sections of the waveguide structure at some of the processing steps of Figure 4.

[0020] Figure 6 is a flow chart of a process for forming a layer with a predetermined concentration profile in accordance with one embodiment of the invention.

[0021] Figure 7 illustrates a curve fit of an experimentally determined concentration of germanium of a film introduced according to six discrete flow rates and a constant silane flow rate.

[0022] Figure 8 illustrates an experimentally determined growth rate of SiGe in a film introduced on a substrate for six discrete germane flow rates and a constant silane flow rate.

[0023] Figure 9 illustrates a selective deposition technique for fabricating waveguide structures in accordance with an embodiment of the invention.

[0024] Figure 10 is a flow chart of the processing steps used to fabricate a waveguide structure using another embodiment of the invention.

[0025] Figure 11 illustrates schematic cross sections of the waveguide structure at some of the processing steps of Figure 10.

[0026] Figure 12 is a flow chart of the processing steps used to fabricate a waveguide structure using yet another embodiment of the invention.

[0027] Figure 13 illustrates schematic cross sections of the waveguide structure at some of the processing steps of Figure 12.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0028] Figure 1 shows a reactor 100 that may be used to fabricate waveguides in accordance with the invention. Reactor 100 may be a commercially available deposition system, such as the EPI Centura system available from Applied Materials, Inc. of Santa Clara, California, modified according to the invention described. It is to be appreciated that the invention is not limited to an EPI Centura system but can be accommodated by other deposition systems.

[0029] Reactor 100 comprises a deposition chamber 12 having an upper dome 14, a lower dome 16 and a side wall 18. Within chamber 12 is a susceptor 20 which extends transversely across chamber 12 dividing chamber 12 into an upper portion 22 above susceptor 20 and a lower portion 24 below susceptor 20. A wafer 99 is supported on the upper surface of susceptor 20. Susceptor 20 is mounted on a shaft 26 that is connected to a motor used to rotate shaft 26, susceptor 20 and wafer 99 thereon.

[0030] An inlet manifold 30 in side wall 18 admits one or more gases into chamber 12. An outlet port 32 in side wall 18 opposite the inlet manifold is used to exhaust gases from chamber 12. A plurality of high intensity lamps 34 mounted around chamber 12 direct their light through the upper and lower domes onto susceptor 20 to heat susceptor 20 and wafer 99 thereon. Lower and upper pyrometers 36 and 40 are used to monitor the temperature of chamber 12. The pressure in chamber 12 is monitored by one or more pressure sensors 42 and regulated by, for example, controlling a vacuum source and a pressure control valve.

[0031] A processor 110 controls the temperature and pressure inside chamber 12. Processor 110 can be a computer chip incorporated into reactor 100 or may be a separate digital computer having executable program instructions. Pyrometers 36 and 40 are coupled to processor 110 thru lines 44. Processor 110 uses received information about the substrate temperature to control heat lamps 34, thereby controlling the substrate temperature. The one or more pressure sensors 42 are also coupled to processor 110 by lines 46. Processor 110 uses received information about the chamber pressure to control the pressure by, for example, controlling a vacuum source and a pressure control valve coupled to chamber 12.

[0032] Figure 1 further shows a gas supply system used to introduce constituents into deposition chamber 12. In one embodiment, the system includes at least two source gas supplies 120 and 122 and a dilutant/inert gas supply 124. Processor 110 controls the introduction of each source gas and the dilutant/inert gas through manifold 30 and controls the flow of each gas through variable flow rate mass flow controllers 160, 162 and 164. The source gases and the dilutant gas can be mixed in chamber 12 or, preferably, pre-mixed before entering chamber 12, as shown in Figure 1. Preferably, the first source gas is a Si source gas, the second source gas is a Ge source gas and the dilutant gas is hydrogen.

[0033] Figure 2 illustrates schematically a waveguide structure 200 that may be fabricated in accordance with an embodiment of the invention. In this embodiment, waveguide structure 200 comprises a substrate 210, a blocking layer 220 formed over substrate 210, and a first graded layer 230 formed over blocking layer 220. Waveguide structure 200 further includes a uniform layer 240 formed over the first graded layer 230, a second graded layer 250 formed over uniform layer 240 and an upper cladding layer 260 formed over the second graded layer 250. Graded layers 230 and 250 have an index of

refraction that varies monotonically with the height of each layer. In particular, the index of refraction increases with height in layer 230 and decreases with height in layer 250.

[0034] The first and second graded layers, 230 and 250, and the uniform layer 240 are composed of a first and second optical materials. The two optical materials are selected such that the index of refraction of the resulting layer varies as the relative concentrations of the two materials changes. In one embodiment of the present invention, the first optical material is a silicon source material and the second optical material is an index of refraction adjusting material, such as germanium. The index of refraction of a SiGe layer is a function of the concentration of Ge in the SiGe layer and increases as the concentration of Ge in the layer increases, *e.g.* a SiGe layer containing 4% Ge will have a higher index of refraction than a SiGe layer containing 2% Ge. The index of refraction of a SiGe layer is adjusted by varying the concentration of Ge in the gases introduced into reactor 100.

[0035] Substrate 210 is any substrate suitable for chemical vapor deposition, such as for example a silicon substrate. Most commercially available substrates contain some amounts of contaminants. During formation of the waveguide structure, these contaminants may diffuse into the waveguide structure and contribute to optical losses in the resulting waveguide structure.

[0036] A blocking layer 220 is used to prevent contaminants from substrate 210 from diffusing into layers 230, 240, 250, 260 during the formation of the waveguide structure. The thickness of the blocking layer 220 is dependent on the amounts of contaminants in the substrate. If substrate 210 contains high levels of contaminants, a thick blocking layer 220 may be needed. If the level of contaminants is low, then a thin layer 220 will suffice. The blocking layer 220 can be any suitable material that prevents contaminant diffusion and has a lower index of refraction than that of the first graded layer 230 at interface A. The blocking layer 220 may be, for example, epitaxial silicon. The blocking layer 220 may not be necessary where the substrate 210 is pure or contains negligible amounts of contaminants.

[0037] As stated above, the first graded layer 230 comprises two optical materials and the concentration of the first optical material increases with the height of the graded layer. The height is measured along a perpendicular to the substrate 210 from the interface of the blocking layer 220 and the first graded layer 230 to the interface of the first graded layer 230 and the uniform layer 240. In one embodiment, the concentration profile along a perpendicular to substrate 210 varies in a linear fashion (see Figure 3(a)). However, other

embodiments where the concentration profile varies in a non-linear fashion are also contemplated (See for example Figures 3(d) - 3(f)).

[0038] In an embodiment of the invention that includes a uniform layer 240, the uniform layer 240 comprises the same two optical materials as used for forming the graded layers, 230 and 250. However, the relative concentrations of the two materials remains constant throughout uniform layer 240. In one embodiment, the relative concentrations of the two materials is the same as the concentration at interfaces B and C of the first and second graded layers 230 and 250, respectively. In other embodiments, the concentrations are selected such that the index of refraction of the uniform layer is higher than both the index of refraction of the first graded layer 230 at interface B and the index of refraction of the second graded layer 250 at interface C.

[0039] The second graded layer 250 comprises the same two optical materials used to form the first graded layer 230 and the uniform layer 240, but the concentration of the first optical material decreases with the height of the second graded layer 250. The height is measured along a perpendicular to the substrate from the interface of the uniform layer 240 and the second graded layer 250 to the interface of the second graded layer 250 and the upper cladding layer 260. In one embodiment, the concentration profile along a perpendicular to the substrate varies in a linear fashion (see Figure 3(a)). However, other embodiments, as described later in connection with Figure 3, where the concentration profile varies in a non-linear fashion are also contemplated (Figures 3(d) - 3(f)).

[0040] In one embodiment, the concentration profiles of the first and second graded layers are symmetric, *i.e.* the rate of decrease of germanium concentration in the second graded layer 250 is the same as the rate of increase of germanium concentration in the first graded layer 230. Other embodiments where the concentration profiles of the first and second graded layers are not symmetric are also contemplated.

[0041] The upper cladding layer is used to confine a light beam propagating in the first graded layer 230, the second graded layer 240, and the uniform layer 250 to the layers 230, 240 and 250. The material for the upper cladding layer is any suitable material with an index of refraction less than that of layers 230, 240, and 250. Preferably, the index of refraction of the upper cladding layer is the same as the index of refraction of the substrate. Preferably, the upper cladding layer is composed of the same material as the substrate 210. The thickness of the cladding layer is selected such that a light beam traveling in layers 230,

240 and 250 effectively sees a cladding layer of infinite thickness. Preferably, the cladding layer thickness is in the range of about 1-20 μm .

[0042] In one embodiment, the waveguide structure 200 does not include the upper cladding layer 260. In this case, the air confines a light beam to layers 230, 240 and 250. In another embodiment, waveguide structure 200 does not include a blocking layer. In yet another embodiment, the waveguide structure 200 does not include uniform layer 240. In this structure, the second graded layer is formed immediately over the first graded layer.

[0043] In other embodiments, the waveguide structure 200 does not include first and second graded layers. Rather, the structure 200 comprises a substrate 210 and a uniform layer 240 formed immediately over substrate 210. Such structure 200 may further include a blocking layer 220 and an upper cladding layer 260. Preferably, layers 220 and 260 are composed primarily of epitaxial silicon.

[0044] In one embodiment, the two optical materials are Si and Ge. In this case, layer 210 is any substrate suitable for Si and Ge deposition. Preferably, the substrate is a silicon substrate. Optionally, a blocking layer is formed on the substrate and comprises epitaxial silicon. The thickness of the blocking layer is typically in the range of about 0-10 μm . A first graded layer 230 is formed on the blocking layer and comprises Si and Ge. In this embodiment, the Ge concentration in the first graded layer increases linearly with height as shown in Figures 3(a) and 3(c). Other Ge concentration profiles, such as those illustrated in Figures 3(d) - 3(f), are also contemplated.

[0045] In this embodiment, the germanium concentration at interface A is about 0% and the germanium concentration at interface B is about 2-5 % and increases with the height of the layer, *i.e.* increases linearly along a perpendicular to the substrate. Typically, the Ge concentration in the first graded layer 230 ranges from about 0% to about 5% and increases at a rate between about 0.1% per μm to about 10% per μm of the height of the graded layer 230. In one embodiment, the Ge concentration in the graded layer 230 increases from about 0% at interface A to about 2% at interface B at a rate of about 5-10% per μm , resulting in a graded layer 230 that is about 0.2 - 0.4 μm thick.

[0046] In this embodiment, the Ge concentration in the uniform layer 240 is in the range of about 2-5 % and the uniform layer thickness is in the range of about 2-5 μm . Preferably, the Ge concentration in the uniform layer 240 is the same as the Ge concentration at interfaces B and C of the first and second graded layers 230 and 250, respectively. In

another embodiment, the Ge concentration in the uniform layer 240 is higher than the Ge concentration at interfaces B and C of the first and second graded layers 230 and 250, respectively. Thus, in this embodiment, the index of refraction of the uniform layer 240 is higher than the index of refraction of layers 230 and 250 at interfaces B and C respectively.

5 **[0047]** The second graded layer 250 comprises Si and Ge where the Ge concentration decreases with the height of the second layer 250. The Ge concentration in the second graded layer 250 is in the range of about 5% to about 0% and decreases at a rate between about 0.1% per μm to about 10% per μm of the height of the second graded layer 250. In one embodiment, the Ge concentration decreases from about 2% at interface C to about 0% at interface D at a rate of about 5-10% per μm , resulting in a second graded layer 250 that is about 0.2 - 0.4 μm thick. Preferably, the concentration profile and the thickness of the first graded layer 230 is symmetrical to the concentration profile and thickness of the second graded layer 250. Preferably, an upper cladding layer 260, composed primarily of epitaxial silicon, is formed on the second graded layer 250.

10 **[0048]** Figure 3 illustrates concentration profiles that may be used to fabricate waveguide structures in accordance with one embodiment of the invention. Figures 3(a), (d) and (f) show concentration profiles of a first optical material, *e.g.* Ge, for exemplary waveguide structures 200 in accordance with three embodiments of the invention that employ a uniform layer 240. In these embodiments, the concentration of the first optical material increases monotonically with height in the first graded layer 230, the concentration remains constant in the uniform layer 240 and the concentration decreases monotonically with height in the second graded layer 250. Optionally, a blocking layer 220 is formed before the first graded layer 230 is formed. These embodiments may also contain an upper cladding layer 260 over the second graded layer 250.

15 **[0049]** Figure 3(b) shows the concentration profile where the structure contains only a uniform concentration layer on substrate 210. This embodiment does not contain first or second graded layers. In this embodiment, the uniform layer 240 is formed directly over substrate 210. The structure may optionally contain a blocking layer between the substrate 210 and the uniform layer 240 and/or an upper cladding layer over uniform layer 240.

20 Figures 3(c) and (e) illustrate concentration profiles of structures that do not contain a uniform layer. In these embodiments, the second graded layer 250 is formed directly over the first graded layer 230. Optionally, a blocking layer 220 is formed before the first graded layer

230 is formed. The structure 200 may also contain an upper cladding layer 260 over the second graded layer 250.

[0050] Figures 4 and 5 illustrate the processing steps used to fabricate waveguide structure 200 in accordance with an embodiment of the invention. Waveguide structure 200 is fabricated using a chemical vapor deposition(CVD) process, preferably, a low pressure chemical vapor deposition (LPCVD) process.

Sub A1 [0051] First, a predetermined pattern 611 is formed on a substrate 210 using standard photolithographic techniques known in the art (Step 510). The substrate 210 is any substrate suitable for opto-electronic device fabrication, preferably Si. Next, the pattern is etched in the substrate 210 using etching techniques known in the art. (Step 515, Figure 5(a)) The substrate surface is then cleaned to remove contaminants, such as native oxides that are formed when the surface of the substrate is exposed to air, prior to placing the etched substrate 210 in the deposition chamber 12. (Step 520). In one such cleaning technique, the substrate is pre-processed by dipping it in a water-based hydroflouric acid solution. The wafer is then placed in the deposition chamber and baked at about 900 C for approximately one minute.

Sub A2 [0052] Where lower temperatures are desired, a dedicated pre-clean chamber such as the one used in the Epi Centura system available from Applied Materials of Santa Clara, CA, may be used to perform the cleaning step. In this case, the wafer is first dipped in a water-based solution of hydroflouric acid. Next, the wafer is placed in the pre-clean chamber and baked at a first temperature for a predetermined time interval and then baked at a second temperature for a second predetermined time interval. In one instance, the first bake is performed at about 750 - 770 C and the second bake is performed at temperatures in the range of about 770-795 C.

Sub A3 [0053] The cleaned substrate 210 is then loaded on susceptor 20 between domes 14 and 16 (Step 530). Next, chamber 12 is heated to the desired temperature using the high intensity lamps 34. (Step 540). Preferably, chamber 12 is heated to a temperature between about 550 C and 1200 C. More preferably, chamber 12 is heated to about 850-1000 C. The first and second source gases 130 and 132 and dilutant gas 134 are next introduced into chamber 12. (Step 550). The pressure in chamber 12 is then adjusted until the desired pressure is reached. (Step 560). For low pressure CVD, the pressure in chamber 12 is maintained below 760 Torr. Although Steps 540, 550 and 560 have been described as having

been performed in a particular sequence, those skilled in the art will recognize that these steps may be performed in any order.

[0054] After the desired pressure and temperature are reached, a series of layers are formed by CVD on substrate 210. Processor 110 controls the introduction of first and second source gases, 130 and 132, used to form films on substrate 210, such as the blocking layer 616 (Figure 5(b)), graded index films 618, 622 (Figure 5(c) and 5(f)), uniform index film 620 (Figure 5(d)), and the upper cladding layer 624 (Figure 5(h)). To fabricate a SiGe waveguide, the first source gas 130 is any suitable source gas that is used for forming silicon films, for example silane, disilane, trisilane, dichlorosilane or trichlorosilane. The second source gas 132 is any source gas used to form germanium films that is compatible with the first source gas 130, for example germane (GeH_4) or digermane. Preferably, the first source gas 130 is silane (SiH_4) and the second source gas 132 is 1% of germane (GeH_4) in H_2 .

[0055] The flow rate of a species into the deposition chamber is one of the factors that determines the growth rate of a layer of film deposited on the substrate. For example, the flow rate of silane determines the growth rate of a silicon layer on substrate 210. These flow rates are regulated by mass flow controllers 160, 162, and 164 that, in turn, are controlled by processor 110 so as to form a desired thickness of each layer. One method for determining the appropriate flow rate of a species and deposition time is described in greater detail below.

[0056] In the case of a SiGe waveguide, processor 110 controls the introduction of silane, germane and hydrogen through mass flow controllers 160, 162 and 164, respectively. For the deposition of the silicon blocking layer 616 (step 570), processor 110 sets mass flow controller 160 in the range of about 10 - 500 standard cubic centimeters per minute (sccm) of silane unit and sets mass flow controller 164 in the range of about 5 - 70 standard liter per minute (slm) of hydrogen unit. Preferably, processor 110 sets mass flow controller 160 to about 50 sccm of silane unit and mass flow controller 164 at about 30-40 slm.

[0057] A first graded SiGe layer 618 is next formed by CVD over blocking layer 616. (Step 572, Figure 5(c)). Any suitable germanium source gas that is compatible with the silicon source gas may be used to form the first graded layer 618, such as commercially available germane or digermane diluted to a suitable concentration. Preferably, silane and 1% germane in H_2 are used to form the first graded SiGe layer 618. In one embodiment, the silane and hydrogen flow rates are maintained at a constant flow rate while the germane

mixture flow rate is increased from 0 sccm to 500 sccm of germane mixture (1% germane in H_2) units based on the desired Ge concentration gradient and the desired final Ge concentration in the first graded layer 618.

[0058] The concentration change of a species, such as germanium, over a height of a film may be accomplished at the mass flow controller 162 by changing the flow rate of the source gas 132 into the chamber 12. However, a linear flow rate change does not necessarily produce a linear concentration gradient of the species in the formed film. Particularly in the case of germane, a linear increase or decrease of the flow rate of germane does not generally result in a linear change in the concentration of Ge in the formed film. Thus, to achieve a linear concentration profile in the formed film, processor 110 controls mass flow controller 162 so as to introduce source gas 132 at a non-linear rate. One technique for forming a desired concentration gradient layer is disclosed in greater detail below in connection with Figure 6.

[0059] Preferably, while maintaining a constant flow rate of silane and H_2 , the germane mixture flow rate is increased from a level of zero that produces a mixture that is 0% germane mixture (1% germane in H_2) / 100% silane to a level that produces a mixture that is 74% germane mixture (1% germane in H_2) / 26% silane. As a result, the Ge concentration in the first graded layer 618 increases at a rate of 5-10% per μm until the final desired Ge concentration is achieved. In the preferred embodiment, the final desired germanium concentration is 2%. Preferably, the silane flow rate into the deposition chamber is maintained at about 40-60 sccm and H_2 flow rate is maintained at about 25-45 slm.

[0060] The uniform SiGe layer 620 is then formed by CVD over the first graded SiGe layer 618 (step 574, Figure 5(d)). Processor 110 controls the flow of silane, germane and hydrogen using mass flow controllers 160, 162 and 164, respectively. In one embodiment, processor 110 uses the growth rate curves calculated in step 720 (See Figure 7) to determine the flow rates of silane 130 and germane 132 for a desired film thickness. Processor 110 introduces silane 130, germane 132 and hydrogen 134 into chamber 12.

[0061] Preferably, the hydrogen flow rate remains constant throughout the deposition and is in the range of about 5 to 70 slm. In one embodiment, processor 110 maintains the silane 130 and germane 132 flow rates constant so as to produce a mixture of about 26% silane and about 74 % germane mixture (1% germane in H_2) with the dilutant H_2 flow rate of about 30-40 slm during the deposition of the uniform layer 620. Processor 110 uses the

growth rates obtained for SiGe having a given Ge concentration to determine the duration of this step.

[0062] The Ge concentration in the uniform layer 620 remains constant, typically between about 2-5% Ge. Preferably, the Ge concentration in the uniform layer 620 matches the Ge concentration of the first and the second graded layers, 618 and 622, at interfaces B and C, respectively. (See Figure 2) In other embodiments, the Ge concentration in the uniform layer 620 may be higher than that of the graded layers 618 and 620 at interfaces B and C, respectively. In this case, the index of refraction of the uniform layer 620 is higher than that of both the first and second graded layers 618 and 622. In one embodiment, the thickness of the uniform layer is in the range of about 2- 5 μm .

[0063] Next, the surface of the deposited uniform layer 620 is planarized to remove those portions of the uniform layer 620, the graded layer 618 and the blocking layer 616 that lie above the plane of surfaces 610, 612. (Step 576, Figure 5(e)). Such planarization may be accomplished, for example, by chemical mechanical polishing. Before performing the planarizing step, the substrate 210 is cooled and removed from the deposition chamber 12. After planarizing, the surface of the substrate 210 is cleaned using the process described in step 520. Steps 530, 540, 550, and 560 are then performed. In another embodiment, the uniform layer 620 fills only region 630 and has a flat top surface similar to surface 632 shown in Figure 5(e). In this case, planarization is not needed.

[0064] Next, a second graded SiGe layer 622 is formed by CVD over uniform layer 620 (Step 578, Figure 5(f)). The second graded layer 622 is formed using a technique similar to that described in step 572 for forming the first graded layer 618. The gas flow rates of relative concentrations are adjusted such that the Ge concentration in the second graded layer 622 decreases with the height of the second graded layer 622. In one embodiment, the Ge concentration profile in the second graded layer 622 is linear. However, other concentration profiles, such as those illustrated in Figure 3(d)-(f) are also contemplated.

[0065] During step 578, the germane mixture flow rate is decreased from 500 sccm to 0 sccm depending on the desired concentration gradient. Preferably, while maintaining silane and H_2 flow rates constant, the germane mixture flow rate into the deposition chamber 12 is decreased from a level that produces a mixture of 74% germane mixture (1% germane in H_2) /26% silane to a level of zero that produces a mixture of 0 % germane mixture (1% germane in H_2) /100% silane. Preferably, the Ge concentration in layer 622 decreases at a rate of

approximately 10% per μm until the final Ge concentration of 0% is achieved, resulting in a second graded layer 622 that is about 0.2 - 0.4 μm . Preferably, the SiH_4 flow rate into the deposition chamber is maintained at about 50 sccm and the H_2 flow rate is maintained at about 30-40 slm.

5 [0066] The second graded layer 622 is then etched to remove the SiGe deposited on surfaces 610 and 612. (Step 580, Figure 5(g). Again, the substrate is cooled and removed from the deposition chamber 12. After etching, the surface of the wafer is cleaned using the process described in step 520. Steps 530, 540, 550 and 560 are then performed and an upper cladding layer 624 is deposited over the second graded layer 622 using the same process
10 conditions as used for forming layer 618. (Step 582, Figure 5(h)). The cladding layer is then planarized if needed. (Step 584, Figure 5(i)).

[0067] For embodiments that contain only the graded layers and do not contain the uniform layer, steps 574 and 576 are not performed. For embodiments that contain only the uniform layer and do not include the first or second graded layers, steps 572, 578 and 580 are
15 not performed. For the embodiments that do not include an upper cladding layer 624, steps 582 and 584 are not performed. And for embodiments that do not have a blocking layer 616, step 570 is not performed.

Forming a concentration gradient layer

20 [0068] Figure 6 illustrates a flow chart for forming a layer with a predetermined concentration profile. In order to form a layer with a desired concentration profile, processor 110 determines the concentration of Ge in a film formed on a test wafer according to a plurality of flow rates of germane through mass flow controller 162. (Step 710). For each flow rate, a corresponding concentration of Ge is measured in the corresponding film formed
25 on the test wafer. Once this data is collected for a plurality of flow rates, a curve is established through a curve fitting algorithm, such as the least square fit method using the Gauss-Jordan algorithm to calculate the coefficients of a polynomial that best fits the experimental measurements. Figure 7 illustrates a curve fit of an experimentally determined concentration of germanium of a film introduced according to six discrete flow rates and a
30 constant silane flow rate.

[0069] Next, the flow rate of germane is measured against the growth rate of the SiGe film introduced on the test wafer. (Step 712) In one embodiment, the experimentally

measured growth rates are measured from the same test wafer used to measure the Ge concentrations. A growth rate curve is established through a curve fitting algorithm, such as the Gauss-Jordan algorithm. Figure 8 illustrates an experimentally determined growth rate of SiGe in a film introduced on a substrate for six discrete germane flow rates and a constant silane flow rate. Although here steps 710 and 712 are performed sequentially, those skilled in the art will appreciate that steps 710 and 712 may be performed in any order or simultaneously.

[0070] The experimentally determined data for the concentration of Ge as a function of flow rate and SiGe growth rate as a function of flow rate are entered into processor 110.

To form the first graded SiGe layer, a desired concentration profile as a function of thickness is entered into processor 110. (Steps 714 and 716). Processor 110 uses the desired concentration profile over the desired thickness as a guide to calculate the set points for mass flow controller 162.

[0071] For a desired concentration, the corresponding germane flow rate is calculated from Figure 7. (Step 718). The flow rate is then used to calculate the SiGe growth rate from Figure 8. (Step 720). This growth rate is used along with a predetermined time interval (Δt) to determine the thickness of a SiGe film for that time interval. (Step 722). Processor 110 then introduces silane 130, germane 132 and hydrogen 134 into chamber 12. Preferably, the flow rates of silane 130 and hydrogen 134 are the same as those used to calculate the germane flow rate and the SiGe growth rate. The germane flow rate is the flow rate calculated from the concentration data points.

[0072] The deposited SiGe film thickness is then subtracted from the total desired thickness to establish the thickness left to be grown. (Step 726). The new thickness and the desired input concentration profile as a function of thickness is used to calculate a new SiGe concentration value. (Step 728). The above process is repeated for this new concentration value for a second time interval. This iterative process is continued until the total desired thickness is achieved.

Calculating the flow rate and deposition time for a species

[0073] Calibration of processor 110 is performed by measuring the thicknesses of a species, such as silicon, on a test substrate for a plurality of flow rates of the source gas and

deposition times. For example, to determine the growth rate of silicon, processor 110 measures the thickness of silicon layers for a plurality of flow rates of silane.

[0074] Processor 110 then determines the thickness as a function of flow rate using curve fitting techniques known in the art, such as least square curve fitting using Gauss-Jordan algorithms (See Figure 7 described in greater detail below). Processor 110 then uses this curve to calculate the appropriate flow rate and deposition time to form a silicon layer of desired thickness. Where the operator specifies a specific flow rate and thickness, processor 110 uses the curve to determine the time interval required to form a silicon layer of a specified thickness.

[0075] Figure 9 illustrates a selective CVD deposition technique for fabricating waveguide structures in accordance with another embodiment of the invention. Generally, in a selective CVD deposition technique, the deposition occurs only on certain regions of the substrate. This is achieved by depositing an oxide layer 1040 on regions where deposition is not needed.

[0076] An etchant gas, such as hydrogen chloride, is introduced into the deposition chamber during the deposition process. The etchant gas removes the deposited layer as it is formed on the substrate. The etch rate and the deposition rate for regions covered by the oxide layer are not the same as the etch rate and the deposition rate for regions not covered by the oxide layer. Thus, selecting the growth conditions such that the deposition rate is lower than the etch rate on the oxide surfaces while the deposition rate is higher than the etch rate on the non-oxide surfaces, results in film deposition only on regions that are not covered by the oxide layer.

[0077] For example, to deposit a layer of SiGe only in region 1030 (Figure 9), surfaces 1010 and 1020 are covered with an oxide layer 1040. The growth conditions are selected such that the rate of deposition of SiGe on the oxide covered surfaces 1010 and 1020 is lower than the rate at which the deposited SiGe is etched from surfaces 1010 and 1020 by the hydrogen chloride. Further, the growth conditions are selected such that the deposition rate of SiGe in region 1030 is higher than the rate at which SiGe is etched in region 1030. Resulting in a SiGe deposition in region 1030 and no SiGe deposition on surfaces 1010 and 1020.

[0078] To form a waveguide structure in accordance with the invention, a pattern is etched into the substrate 210 using, for example, the method described earlier in steps 510

and 515 (Figure 5 and Figure 9(a)). Using commonly known techniques in the art, an oxide layer 1040 is then deposited on surfaces where either Si or SiGe deposition is not needed, *e.g.* surfaces 1010 and 1020 of the patterned etched substrate. (Figure 9(b)). The oxide layer 1040 allows deposition in region 1030 without deposition on surfaces 1010 and 1020.

5 [0079] Next, the substrate 210 is cleaned as described in step 520. (Figure 5). Steps 530 thru 550 are then performed as described earlier. The first graded layer 930, the uniform layer 940, and the second graded layer 950 are then deposited in region 1030 using the techniques described earlier in steps 572, 574, and 578, respectively. (Figure 5 and Figures 9(c) - 9(e)).

10 [0080] Preferably, the source gases for the formation of the waveguide structure are germane, dichlorosilane, hydrogen chloride, and hydrogen. The relative concentrations of these gases, the temperature and the pressure are selected such that the deposition rate of Si and SiGe in regions 1010 and 1020 is lower than the etch rates of Si and SiGe in those regions while the deposition rate of Si or SiGe in region 1030 is higher than the etch rate of Si or SiGe in region 1030. After the waveguide structure is deposited, the oxide layer 1040 is removed using techniques known in the art (Figure 9(f)).

15 [0081] Although the embodiment shown in Figure 9 does not show a blocking layer or an upper cladding layer, those skilled in the art will appreciate that embodiments containing the blocking and cladding layers in addition to the first graded layer 1060, the uniform layer 1062 and the second graded layer 1064 may be formed using the process described above. For embodiments that contain only the graded layers, 1060 and 1064 and not the uniform layer 1062, steps 574 and 576 are not performed. For embodiments that contain only the uniform layer 1062 and do not include the first or second graded layers 1060 and 1064, steps 572, 578 and 580 are not performed. For embodiments that do not include an upper cladding layer, steps 582 and 584 are not performed. And for embodiments that do not have a blocking layer, step 570 is not performed.

20 [0082] Figures 10 and 11 illustrate another technique for fabricating waveguide structures in accordance with the invention. Figure 10 shows the processing steps that may be executed to form a waveguide structure. Figure 11 illustrates schematic cross sections of the waveguide structure at some of the processing steps of Figure 10. Steps 1110 - 1140 are performed using similar techniques as described in steps 510 - 560 of Figure 4. A blocking layer 1210 is next deposited on substrate 210 using CVD. (Step 1150, Figure 11 (a)). A first

25

30

graded layer 1220 is then formed over the blocking layer 1210. (Step 1160, Figure 11(b)). Next, the uniform layer 1230 is formed on the first graded layer 1220. (Step 1170, Figure 11(c)). The methods for forming the blocking layer 1210, the first graded layer 1220 and the uniform layer 1230 are similar to those described earlier in connection with Figures 5 and 6.

5 [0083] After the uniform layer 1230 is formed, the substrate 210 is cooled and removed from chamber 12. A pattern is formed over the uniform layer 1230 using techniques known in the art. (Step 1172). The uniform layer 1230 and the first graded layer 1220 are then etched using techniques known in the art. (Step 1174, Figure 11(d)). The etched patterned substrate is then cleaned using techniques similar to those described earlier in step 10 520 (Figure 4) and placed in chamber 12. Steps 1115 - 1140 are performed again. An oxide layer 1240 is next deposited over blocking layer 1210 as shown in Figure 11 (e). (Step 1176). The oxide layer 1240 is formed by introducing a silicon gas source and oxygen into chamber 12.

15 [0084] A second graded layer is then formed around the etched patterned uniform layer 1230 and graded layer 1220 as shown in Figure 11(f). (Step 1178). The flow rates of the gases (silane, germane, hydrogen and hydrogen chloride), the temperature, and the pressure are selected such that the second graded layer 1250 is only formed around surfaces 1252, 1254, and 1256 (Figure 11(e)). The deposition rate on surfaces 1252, 1254, and 1256 is higher than the etch rate on those surfaces. Additionally, the flow rates of the gases (silane, 20 germane, hydrogen and hydrogen chloride), the temperature, and the pressure are selected such that a second graded layer is not formed on oxide surfaces 1242 by selecting these parameters so that the deposition rate on surfaces 1242 is lower than the etch rate on surfaces 1242.

25 [0085] The oxide layer 1240 is then removed using techniques known in the art. (Step 1180, Figure 11(g)). A cladding layer 1260 is then formed over the second graded layer 1250 and the blocking layer 1210, as shown in Figure 11(h). (Step 1182). The surface of the cladding is then planarized to form the structure shown in Figure 11(i). In other embodiments, the planarization step may not be necessary where the cladding layer is grown so as to form a flat surface 1262 (see Figure 11(h)) or where a flat surface 1262 is not 30 required.

[0086] For embodiments that contain only the graded layers and not the uniform layer, step 1170 is not performed. In this embodiment, steps 1172 and 1174 are performed

immediately after step 1160. For embodiments that contain only the uniform layer 1230 and do not include the first or second graded layers 1220 and 1250, steps 1160, 1176, 1178 and 1180 are not performed. For the embodiments that do not include an upper cladding layer 1260, steps 1182 and 1184 are not performed. And for embodiments that do not have a blocking layer 1210, step 1150 is not performed.

[0087] Figures 12 and 13 illustrate yet another technique for fabricating waveguide structures in accordance with the invention. Figure 12 shows the processing steps that are executed to form a waveguide structure in accordance with this embodiment. Figure 13 illustrates schematic cross sections of the waveguide structure at some of the processing steps of Figure 12. Steps 1310 - 1360 are performed using techniques similar to those described in steps 510 - 560 in connection with Figure 4. Next, a uniform layer 1410 is formed epitaxially by CVD on substrate 210. (Step 1370, Figure 13(b)). The method for forming the uniform layer 1410 is similar to that described earlier in step 574 in connection with Figures 4 and 5.

[0088] After the uniform layer 1410 is formed, the substrate 210 is cooled and removed from chamber 12. The surface of the deposited uniform layer 1410 is then planarized to remove those portions of the uniform layer 1410 that lie above the plane of surfaces 1440 and 1450. (Step 1372, Figure 13(c)). Such planarization may be accomplished using techniques commonly known in the art, such as, chemical mechanical polishing. After planarizing, the surface of the substrate 210 is cleaned using the process described earlier in step 520. Steps 1330, 1340, 1350, and 1360 are then performed. In another embodiment, the uniform layer 1410 is formed by filling only region 1460 and has a flat top surface similar to surface 1470 shown in Figure 13(c). In this case, planarization is not needed.

[0089] A graded layer 1420 is then formed epitaxially by CVD over uniform layer 1410 as shown in Figure 13(d). (Step 1374). The method for forming the graded layer 1420 is similar to that described earlier in step 578 in connection with Figures 4 and 5. The gas flow rates of relative concentrations of silane and germane are adjusted such that the Ge concentration in the graded layer 1420 decreases with the height of the graded layer 1420. In one embodiment, the Ge concentration profile in the graded layer 1420 is linear. However, other concentration profiles, such as those illustrated in Figure 3(d)-(f) are also contemplated.

[0090] Next, a cladding layer 1430 is formed epitaxially by CVD over the second graded layer 1420. (Step 1376). The method for forming the cladding layer 1430 is similar to that described earlier in step 582 in connection with Figures 4 and 5.

[0091] The structure described immediately above does not include a transition layer between the substrate 210 and the uniform layer 1410. The concentration of Ge almost instantaneously increases from about 0% in the substrate 210 to its percentage (typically, about 2-5%) in uniform layer 1410. In this case, the growth conditions, *i.e.* desired temperature, pressure and concentrations of constituent gases for achieving the desired Ge concentration are established almost instantaneously.

[0092] Other embodiments may include a transition layer formed epitaxially between the substrate 210 and the uniform layer 1410, such as a transition layer similar to the first graded layer 618 described earlier in connection with Figure 4 (step 572) and Figure 5 (e). In one embodiment, the gradient of the layer is such that the concentration of Ge increases from about 0% to about 2-5% at a rate of about 10% per μm , forming a transition layer that is about 0.2 - 0.5 μm thick. During formation, the flow rate of source gas 132 is gradually increased, such that the Ge concentration in the transition layer increases at a rate of about 10% per μm .

[0093] In yet other embodiments, the Ge concentration may increase very rapidly, forming a very thin transition layer, *e.g.* the transition layer, for example, may be only about 0.01 μm to about 0.05 μm thick. For example, to form a 0.01 μm thick transition layer where the Ge concentration increases from about 0% to about 2%, the Ge concentration in the transition layer must increase at a rate of about 200% per μm . This is achieved by increasing the flow rate of source gas 132 very rapidly.

[0094] Similarly, in one embodiment, the Ge concentration in the graded layer 1420 may be decreased very rapidly in a manner similar to that described immediately above for the transition layer. In this case, the graded layer 1420 is very thin and may be only 0.01 μm to 0.05 μm thick.

[0095] In yet another embodiment, the waveguide structure may be formed by forming the cladding layer 1430 immediately over the uniform layer 1410. In this case, the structure does not include a graded layer 1420 and step 1374 is not performed. The Ge concentration profile is similar to that shown in Figure 3(b). That is, the Ge concentration immediately decreases from its percentage in the uniform layer 1410 to 0% in the upper cladding 1430.

[0096] While the present invention has been described with reference to a few specific embodiments, the description is illustrative of the invention and is not to be construed as limiting the invention. For example, the waveguide structure disclosed is a SiGe waveguide structure but those skilled in the art can appreciate that the processes disclosed may be employed for waveguide structures made of other materials. Further, various modifications of the structures described may occur to those skilled in the art without departing from the true spirit and scope of the invention as defined by the appended claims.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2